



BIO PROTETTIVO MIX



BIO.PRO.MIX 1

BIO.PRO.MIX 5

BIO.PRO.MIX 25



PRODUCT DESCRIPTION

Naturalcalk Bio Protettivo Mix does not allow infiltration of water and oil; it is used on vertical and horizontal surfaces, outdoor/in-door, and it does not change the appearance of the treated surface. It does not contain V.O.C. and keeps the surface breathability.

FIELDS OF USE AND PRODUCT APPLICATION

Before applying the Naturalcalk Bio Protettivo Mix, always test it on a small area of the surface. Surfaces quality: preparation with products from the Natural Calk line. Humidity must not exceed 10% at a depth of 1 cm.

The surface must be clean, free of dust, dirt of any kind, oil, efflorescence, mold, and old paint. Treat with natural antibacterial fungicide.

On vertical surfaces, make sure to apply the product from the bottom up, preferably by a brush with a low-pressure spray, to ensure good protection from applying the product by refuse.

PRODUCT FEATURES AND BENEFITS

Naturalcalk Bio Protettivo Mix prevents dust, oil stains, chewing gum, and graffiti from adhering to the surface and prevents smog from adhering as well. On surfaces, it does not have a film effect, and it does not change the appearance and color. Furthermore, the treated surface does not absorb humidity, mist, or steam.

Naturalcalk Bio Protettivo Mix is easy to apply on any kind of building surfaces and can be walked on after one hour for horizontal surfaces. It prevents seasonal deterioration due to freeze-thaw effect, and the treated surface reduces maintenance costs.

Why should you choose Naturalcalk Bio Protettivo Mix?

- It is resistant to UV rays.
- It is not flammable.
- It is not toxic.
- It is eco-sustainable.
- It helps improve thermal insulation in the surfaces by 15%, thanks to the protection from water that causes the worsening of the transmittance.

EMPFEHLUNGEN

Naturalcalk Bio Protettivo Mix cannot be applied in two coats due to the first coat drying out; it does not guarantee good adhesion and is guaranteed on absorbent surfaces. In the presence of moss or mold, treat the surface with a natural antibacterial fungicide before applying the Naturalcalk Bio Protettivo Mix. The exclusive use of the products of the Natural Calk line is absolutely strict in every processing phase of the Tiliica Pasta system in order to maintain the characteristics of the system and guarantee the result.

The company takes on sole responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri SRL, while the application, use, and processing are the exclusive responsibility of the customer or the applicator. The company reserves the right to modify the composition, keeping the characteristics naturally unchanged.

