



# PUTTY LIME

MAP.GRASS



## PRODUCT DESCRIPTION

Naturalcalk Grassello di Calce (putty lime), obtained from sawing stone cooking in industrial furnaces with various mineral characteristics, aged in tanks to obtain a balanced aging.

## FIELDS OF USE AND PRODUCT APPLICATION

Protect the Naturalcalk putty lime application from the rain for about 48 hours.  
Do not apply at air temperatures below 5°C or higher than 25°C and on walls overheated by the sun; in hot and breezy periods, it is necessary to moisten the walls.  
Before use, shake mechanically until the mixture is homogeneous, and, if the bricks or the wall are too dry, moisten with water.

## PRODUCT FEATURES AND BENEFITS

Naturalcalk putty lime follows the UNI EN 459-1:2002 standard and is classified in the first class (CL 90).

### Why should you choose Naturalcalk putty lime?

- Excellent plasticity and good yield.
- Recommended for works and restorations bound by superintendents.
- Excellent in traditional building.
- Valid for floors and floors lightened with natural aggregates (expanded clay, pumice, cork).

The yield may vary according to the granulometry and type of the aggregate, on average it is kg cm 125-250.

## WARNINGS

The exclusive use of the products of the Natural Calk line is absolutely strict in every processing phase of the Tillica Pasta system in order to maintain the characteristics of the system and guarantee the result.

The company takes on solely responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri SRL while the application, use, and processing are the exclusive responsibility of the customer or the applicator. The company reserves the right to modify the composition, keeping the characteristics naturally unchanged.

