



MARMORINO

FIN.MARM.BIANCO.C100

FIN.MARM.BIANCO.C200

FIN.MARM.COL.C100

FIN.MARM.COL.C200

PRODUCT DESCRIPTION

Naturalcalk Marmorino is the finishing layer of plaster (fixing) for interiors or exteriors, produced with wood-fired magnesium putty lime according to UNI EN 459-1 standards and naturally aged for long times in tanks. Mixed with limestone, marble grits, carbonates, colored earth, and inorganic pigments; not subject to shrinkage, resistant to alkaline aggression and salt air, it does not dust.

Naturalcalk Marmorino is ready to use and is supplied white or in the color chosen by the customer.

Already colored, it avoids the need for a further layer of tinting but it can still be tinted, with Naturalcalk Tinta al Latte di Calce.

Naturalcalk Marmorino is supplied in two granulometers: C100 and C200, to be applied in two or more layers depending on the type of processing required. It can be worked with a trowel and sponge, sbladed and spatulated.

Due to its natural and ecological composition and the total absence of chemical additives, Naturalcalk Marmorino is particularly suitable for bio-architecture interventions and the restoration of artistic and historical heritage.

FIELDS OF USE AND PRODUCT APPLICATION

Naturalcalk Marmorino is used in the Naturalcalk Tillica Pasta System as a possible finishing layer of Tillica Pasta, smoothed in two coats, after the application of Naturalcalk Fissativo Antibatterico if required.

The application procedure and the drying time between one coat and the other and of the entire finishing layer of Naturalcalk Marmorino may vary according to the type of processing and weather conditions.

PRODUCT FEATURES AND BENEFITS

Its average yield may vary in relation to the absorption of the support, with granulometry C.200: 3-4 kg/sqm and with C.100 granulometry: 2-2.5 kg/sqm for one coat.

Why should you choose Naturalcalk Marmorino?

- It is ready to use
- It has excellent breathability μ 4.5;
- It resists salt air
- It is not subject to pullbacks
- Fireproof material
- Resists alkaline aggression
- It does not dust
- Specific weight 1.7 kg/l/pH 12
- It is a recyclable solution
- It persists over time

WARNINGS

Naturalcalk Marmorino shall not be applied with temperatures of the atmosphere or of the support below 7°C or higher than +30°C; be careful to use in excessively ventilated environments or those at risk of quick drying, and protect from strong temperature changes. During drying, protect from frost and rain.

The exclusive use of products from the Naturalcalk line in each layer of the Tillica Pasta System is absolutely strict to maintain the characteristics of the system and guarantee the result.

The company takes on solely responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri Srl while the application, use, and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged.

