



PASTELLA

PAV.PSTLLA

PRODUCT DESCRIPTION

Naturalcalk Pastella is used for the formation of pastelloni, in perfect accordance with the requests of the Superintendences of Environmental and Cultural Heritage; it is used both in the implementation of finishes and recovery of historical buildings. Due to its natural and ecological composition and total absence of chemical additives, it's particularly suitable also for bioarchitectural implementations.

Naturalcalk Pastella is produced with selected lime putty naturally aged for a long time in tanks, produced by wood cooking according to UNI EN 459-1 standards, of limestone and marble grits, colored soils, and inorganic pigments.

FIELDS OF USE AND PRODUCT APPLICATION

The Naturalcalk Pastella should be applied with a stainless-steel floating and finished with slim. If the surface is dusty, apply a coat of Naturalcalk Primer.

During drying, protect from frost and heat and do not apply on cold days, not lower than 7°C on hot or ventilated days.

By using the Naturalcalk Pastellina at the end, shaded and silky effects can be obtained. Before use, shake mechanically at low speed until the mixture is homogeneous.

PRODUCT FEATURES AND BENEFITS

The average consumption of Naturalcalk Pastella is 1.5kg/-sqm/1mm, but it may vary in relation to the nature and absorption of the support. Supplied in 25 kg drums.

WARNINGS

The exclusive use of the products of the Natural Calk line is absolutely strict in every processing phase of the Tillica Pasta System in order to maintain the characteristics of the system and to guarantee the result.

The company takes on solely responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri Srl while the application, use, and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged.

