



PRIMER 12

PRIM12-1

PRIM12-5

PRIM12-25



PRODUCT DESCRIPTION

Naturalcalk Primer 12 is ideal for rustic and civil plasters, flaked plasters, old wall surfaces, porous and absorbent supports. The product has excellent penetration, consolidation, and transpiration characteristics of the support.

Naturalcalk Primer 12 gives compactness to the plaster, thus facilitating the anchoring of lime-based products, ancient grouts, smoothing, thick paints, glazed decorations. It is a product that has no odor, it is not flammable, it does not harm to man or the environment.

FIELDS OF USE AND PRODUCT APPLICATION

Naturalcalk Primer 12 can be used on internal and external walls, particularly suitable as a base coat for smoothing, antique stucco, decorative plaster.

Naturalcalk Primer 12 is ready to use, it must be applied in one coat with a brush or roller. The drying time is 1-2 hours, for total drying 10-12 hours at a temperature of 20°C with humidity 70%.

PRODUCT FEATURES AND BENEFITS

Naturalcalk Primer 12 is composed of white spirit. Storage temperature: +2°C- +35°C (protect from frost). We recommend the normal precautions for the handling of products in water solution. For the storage and handling, there are no particular precautions; containers, residues, and any spills must be collected using inert absorbent materials such as sand and soil that must be disposed of in accordance with the national or regional provisions in force. Transport must be in compliance with international agreements.

Why should you choose Naturalcalk Primer 12?

- It has no odor
- It is not flammable
- It does not harm to man and the environment
- Specific weight 1kg/L

WARNINGS

The exclusive use of the products of the Natural Calk line is absolutely strict in every processing phase of the Tillica Pasta System in order to maintain the characteristics of the system and to guarantee the result.

The company takes on sole responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri Srl while the application, use, and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged.

