



PATINA

PRO.PATINA

PRODUCT DESCRIPTION

Naturalcalk Patina is an emulsion of vegetable oils and resins, thick enough to apply on the floor. All components are exclusively and strictly of vegetable origin.

100% natural oil and resin finish, of vegetable origin, with high solids for the treatment of parquet and other surfaces. Its simplicity of use makes it particularly suitable for the do-it-yourself. The product is free from cobalt and butanone oxime.

PRODUCT APPLICATION

After using the fine grain abrasive, remove the dust perfectly with a vacuum cleaner and an antistatic cloth or a wet cloth.

Shake the product in the tin to dissolve any sediment formed on the bottom. Apply the product evenly using a roller or sponge or squeegee (natural sponge): the product must be well applied and made to penetrate the floor with the simple pressure of the hand. For the professional installer, apply the product on the floor and pull it evenly with the single brush (brush without teeth). Sometimes one coat of Naturalcalk Patina is enough. If after one hour or more, the first coat seems not sufficient, a light second coat can be applied evenly, thus removing the excess part with paper.

To promote drying, it is recommended to use small quantities of the product, the protection of the floor is guaranteed thanks to the high solid residue. The treated floor can feel dry to the touch after one hour and in any case at the most within 24 hours, depending on the support, the climatic conditions, and the quantity of the product applied. The optimal resistance to liquid substances occurs after 15 days from the first application because the oxidation and carbonation process begins to consolidate the treatment.

PRODUCT MAINTENANCE

To clean the painted floor, remove dust with cotton clothes. Do not use microfiber clothes as they are already "degreasing" in themselves and in the long time, they remove the vegetable oil finish. It is recommended to periodically clean the floor treated with Naturalcalk Patina with Calksap, the delicate soap that reinvigorates the treatment, avoiding or postponing out extraordinary floor maintenance.

Do not use detergents or aggressive agents available on the market. Washing with chemical products called "Marseille soap" can affect the appearance of a freshly treated floor; therefore, we recommend only and exclusively Calksap or the appropriate soap for cleaning treated floors.

WARNINGS

In the event of low ambient temperatures, the drying times may long. The final aesthetic result of the application can be evaluated not before two or three days from the end of the application. The treated surface will be walkable to walk on, if dry, after 24 hours and reaches optimal mechanical and stain resistance resistances after 15 days. Unlike other oil-based products on the market, rags soaked in the patina are not subject to self-combustion.

The rags must in any case be managed following the regulations on waste. Yield is variable and depends on the absorption and on the "hand" of the user. Indicatively, the optimal yield is around 25-30 sqm/L.

The exclusive use of the products of the Natural Calk line is absolutely strict in every processing phase of the Tilla Pasta System in order to maintain the characteristics of the system and to guarantee the result.

The company takes on sole responsibility for the product up to the departure of the material from the deposit/supplier Arte e Mestieri Srl while the application, use, and processing are the exclusive responsibility of the customer or the applicator.

The company reserves to modify the composition keeping the characteristics naturally unchanged.

